

<text><text><text><text><text><text><text><text>

| Specifications | |
|--------------------------------------|---|
| Motor | 18V Brushless motor |
| Battery | Compatible with all 18V batteries and the BSL36A18 battery |
| Pump | 1 plunger pump (HiKOKI original) |
| Water pressure | 5-20 bar |
| Tank capacity | 8 |
| Water consumption | 0.5-1.2 l/min. |
| Continuous operating time per charge | 35 min. (using a 5.0 Ah battery) |
| Original short nozzle | Straight and wide spray |
| Hose length | 3 m |
| Battery Indicator | Yes |
| Water filter | Yes |
| Weight ² | 4.8 kg |
| | |

| Characteristics | |
|--|--|
| Powerful washing: 20 bar water pressure | |
| Variable pressure control | |
| Easy to use for many kinds of washing applications | |
| One plunger pump | |
| Compact and lightweight design | |
| Easy water charging by separable tank | |
| | |

Standard accessories¹

Trigger gun unit Variable nozzle High pressure hose (3 m) Nozzle cleaner pin

¹ Standard accessories vary by country or area.

² Weight without water in tank. According to EPTA-Procedure 01/2014. Read everything about our services at **hikoki-powertools.co.uk**



Non-contractual presentation photos, the machines are delivered without accessories unless otherwise stated. HiKOKI reserves the right to change certain technical characteristics, as well as the accessories supplied as standard. All products presented fall within the limit of the available stocks of HiKOKI Power Tools.