

## AL18DA

### Cordless Grease Gun

18V / 690 bar

- 10 STAGES FOR CLEAN WORKING
- OPTIONAL HIGH PRESSURE WITH MAX. 690 BAR
- HIGH DISCHARGE VOLUME OF 297 ML/MIN.
- 3-WAY FILLING



 Compatible

#### Specifications

Voltage		18V
Grease capacity		400 g
Max. pressure	High	690 bar
	Low	414 bar
Discharge pressure	High	297 ml/min.
	Low	100 ml/min.
Runtime <sup>1</sup>	Gear 1	2300 ml
	Gear 2	3800 ml
Vibration level		1.43 m/s <sup>2</sup>
Length of hose		1.2 m
Weight without battery <sup>2</sup>		4 kg

#### Features

Presetting of the discharge volume: thumbwheel with 10 stages for clean working, including continuous delivery (no preload)

2 work stages: optional high pressure with max. 690 bar or high discharge volume of 297 ml/min.

3-way filling: grease cartridge, container or direct filling possible

Optimal view, also in the darkest of corners, with a LED directly on the housing and other LEDs for fixing to the hose end

Possibility to use it with adapters (no standard scope of delivery) to use it also with cartridges (System Reiner and Lube Shuttle)

#### Versions<sup>1</sup>

AL18DAW4Z: 4966376414871	Cardboard box
-----------------------------	---------------

<sup>1</sup> With battery BSL1820M

<sup>2</sup> Weight according to EPTA-2004 procedure.

<sup>3</sup> Standard accessories vary by country or area.

Read everything about our services:  
[hikoki-powertools.co.uk](https://www.hikoki-powertools.co.uk)