



Specifications		
Voltage		36V
Handle type		Loop handle / bike handle
Cutting capacity	Nylon head	440 mm
	Blade	255 mm
No-load speed	Power mode	6,000 rpm
	Auto mode	4,700 rpm
	Eco mode	3,000 rpm
Runtime with blade ¹	Power mode	27 min.
	Auto mode	50 min.
	Eco mode	115 min.
Runtime with nylon head ¹	Power mode	10 min.
	Auto mode	24 min.
	Eco mode	80 min.
Anti-kickback function		\checkmark
Spindle lock		\checkmark
Dimensions (L x W x H)	Loop handle	1,840 x 340 x 193 mm
	Bike handle	1,840 x 627 x 482 mm
Weight ²	Loop handle	4.9 kg
	Bike handle	5.1 kg

Characteristics

Usable with nylon head or metal blades for various applications

Perfectly balanced due to motor location at the rear of the machine
for less fatigue and easy swinging

High torque for powerful cutting operation

Equipped spindle lock for conveniently mounting cutting attachements

Auto mode which automatically regulates the cutting speed

Long runtime of up to 115 minutes per charge (4.0 Ah) for large areas Brushless motor for high power, less wear and a long service life

Versions ³	
CG36DCW4Z: 4966376413994	Loop handle, Tap & go nylon head, 3 teeth metal blade, blade cover, harness, wrench set, cardboard box
CG36DCW5Z: 4966376414007	Bike handle, Tap & go nylon head, 3 teeth metal blade, blade cover, harness, wrench set, cardboard box

Read everything about our services at **hikoki-powertools.eu**



¹ Runtimes using BSL36A18X.

² Weight according to EPTA-2004 procedure.

³ Standard accessories vary by country or area.