

NEW

CV350V2
Multitool
230V - 350 W

Updated locking mechanism

Wide range of accessories available

350 W motor with overload protection



Specifications

Voltage	230V
Input power	350 W
No-load oscillation frequency	6,000 - 20,000 /min.
Oscillating angle	3.2°
Accessory system	OIS (Starlock compatible)
Variable speed	✓
Toolless accessory change	✓
Soft start	✓
Constant speed control	✓
Auto mode	✓
Cord length	2.5 m
Dimensions (L x H)	280 x 100 mm
Weight ¹	1.5 kg

Characteristics

- Updated locking mechanism for a fast tool-free change of accessories
- Wide range of optional HiKOKI accessories available
- 350 W motor with overload protection for a fast and durable working process
- Variable speed regulation for the right speed for each application
- Non-snapping, very smooth closing accessory locking lever for safe change of accessories

Versions²

CV350V2J1Z: 4966376412563	Cutting blade wood/metal, sanding pad, 10x sanding paper (P80, P120), stackable case HSC II
CV350V2J2Z: 4966376412570	Cutting blade wood/metal, sanding pad, 10x sanding paper (P80, P120), stackable case HSC II

¹Weight according to EPTA-2004 procedure.

²Standard accessories vary by country or area.

Read everything about our services at hikoki-powertools.co.uk

