



## EC36DA

**Cordless Compressor** 

36V - 9.3 bar - 7.3 L

Lightweight and compact design

Powerful motor refills the tank within 17 seconds

Oil-free and Brushless Motor technology





Specifications	
Voltage	36V
Motor type	Brushless
Tank shape	Hotdog
Tank capacity	7.3 L
Cut-in pressure	7.2 bar (105 PSI)
Cut-off pressure	9.3 bar (135 PSI)
Air delivery at 2.8 bar	65.1 L/min.
Air delivery at 6.2 bar	45.3 L/min.
Air filling time <sup>1</sup>	65 sec.
Air refilling time <sup>1</sup>	17 sec.
Working capacity per charge <sup>2</sup>	Over 1,000 nails
Oil-less lubrication	$\checkmark$
External intake filter	$\checkmark$
Dimensions (L x W x H)	408 x 330 x 343 mm
Weight with BSL36B18 <sup>3</sup>	14.3 kg

## Characteristics

Lightweight and compact design for easy portability making it ideal for finish and trim work without the constraints of an extension cord

Oil-free and Brushless Motor technology, along with the removable air filter, ensure easy maintenance and a longer tool lifetime

Powerful motor refills the tank to its max. pressure of 9.3 bar within 17 seconds  $\,$ 

Large pressure knob and easy-to-read gauges

All-metal roll cage design for greatest durability

Big tank capacity of 7.3 L to shoot more than a 1,000 brad nails with one battery charge  $\,$ 

## Version

EC36DAW4Z: 4966376414802

Cardboard box

Read everything about our services at hikoki-powertools.co.uk



 $<sup>^{\</sup>scriptsize 1}$  When using battery BSL36B18.

<sup>&</sup>lt;sup>2</sup>When using 18 Gauge Brad Nailer NT50AE2 with battery BSL36B18.

<sup>&</sup>lt;sup>3</sup> Weight according to EPTA-2004 procedure.