



## BSL36A18X MULTI VOLT Battery 36/18V - 2.5/5.0 Ah

Powers 18V and 36V tools

High power output

Improved water and drop resistance





	Specifications	
	Voltage	36/18V
	Capacity	2.5/5.0 Ah
	Energy	2x 45 Wh
	Battery level indicator	$\checkmark$
	Charging time with UC18YSL3	32 min.
	Charging time with UC18YFSL	75 min.
	Numbers of cells	10
	Cell size (Ø x L)	18 x 65 mm
	Dimensions (L x W x H)	118 x 80 x 71 mm
	Weight <sup>1</sup>	740 g

## Characteristics

Automatic Switching System - Intelligent circuitry changes voltage automatically to power all 18V and 36V HiKOKI tools

36 V nominal voltage and up to 41 V after charging allowing the batteries to deliver the power to increase productivity and efficiency

Intelligent electronics ensures constant communication between tool, battery and charger to prevent overload, overheating, overcharge and overdischarge for longest battery and tool life

Improved water resistance and drain outlets for prolonged lifetime

15% improved shock resistance via dual-layer elastomer base guarding against drops and surface damage

Integrated 4-LED display shows remaining battery charge to prevent costly downtime on the job

Higher power output achievable than with similar sized 18V batteries

## Versions<sup>2</sup>

**380082**: 1x MULTI VOLT BSL36A18X battery, 4549115282827 cardboard box

<sup>1</sup>Weight according to EPTA-2004 procedure.

<sup>2</sup> Standard accessories vary by country or area.

Read everything about our services at **hikoki- powertools.co.uk** 

hikoki-powertools.co.uk

