HíKOKI

NR1890DCA

18V Cordless 30 Degree Clipped Head Framing Nailer

- LIGHTWEIGHT & COMPACT
- HIGH AND FAST DRIVING POWER
- NEW AGGRESSIVE NOSE FOR BETTER TOENAILING
- NO GAS/NO HOSE/NO COMPRESSOR



Specifications

| • | |
|------------------------------------|--|
| Voltage | 18V |
| Type of Motor | Brushless |
| Driving System | Air Spring |
| Nail Length | 50 to 90 mm |
| Applicable Nails Shank Diameter | 2.9 to 3.3 mm |
| Driving Speed | Up to 2.7 nails/sec. |
| Driving Mode ¹ | Full sequential / Contact |
| Nail Capacity | 50 nails |
| LED Light | Yes |
| Long Magazine | Yes, Optional |
| Applicable Nail Shank Diameter | 2.9 to 3.3 mm |
| Depth Adjustment | Tool-free |
| Nail Collation Angle | 30° to 34° |
| Rafter Hook | Yes |
| Dimensions (H $x L x W$) | 359 x 315 x 133 mm (with BSL1850MA battery) |
| Weight ² | 4.4 kg (With BSL1850MA battery) |

Versions³

NR1890DCAJPZ: 4966376415943

2x battery BSL1850MA, Charger UC18YSL3, Stackable System Case 4, rubber nose

NR1890DCAW9Z: 4966376415967

Stackable System Case 4, rubber nose

Features

Air-spring drive system, for smooth, pneumatic-like feel.

Improved more compact, lightweight design for ease of use and optimal control.

High-powered to surely drive up to 90mm nails.

Improved more aggressive nose prevents slippage on angled shots, for better skew nailing.

Easy-to-access control panel for ease of operation.

Bright LED for better visibility in dark or confined spaces.

¹ For NR1890DCAW3Z: Full sequential mode only

² Weight: According to EPTA-Procedure 01/2024

³ Standard accessories vary by country or area.



Non-contractual presentation photos, the machines are delivered without accessories unless otherwise stated. HiKOKI reserves the right to change certain technical characteristics, as well as the accessories supplied as standard. All products presented fall within the limit of the available stocks of HiKOKI Power Tools.